

Attachment 1

The San Juan Basin

The San Juan Basin covers an area of about 7,500 square miles across the Colorado/New Mexico line in the Four Corners region (Figure A1-1). It measures roughly 100 miles long in the north-south direction and 90 miles wide. The Continental Divide trends north-south along the east side of the basin, and land surface elevations within the basin range from 5,100 feet on the western side to over 8,000 feet in the northern part.

The San Juan Basin is the most productive coalbed methane basin in North America. Coalbed methane production in the San Juan Basin totaled over 800 billion cubic feet (Bcf) in 1996 (Stevens et al., 1996). This number rose to 925 Bcf in 2000 (GTI, 2002). The coals of the Upper Cretaceous Fruitland Formation range from 20 to over 40 feet thick. Total net thickness of all coalbeds ranges from 20 to over 80 feet throughout the San Juan Basin. Coalbed methane production occurs primarily in coals of the Fruitland Formation, but some coalbed methane is trapped within the underlying and adjacent Pictured Cliffs Sandstone, and many wells are completed in both zones. Coalbed methane wells in the San Juan Basin range from 550 to 4,000 feet in depth, and about 2,550 wells were operating in 2001 (CO Oil and Gas Conservation Commission and NM Oil Conservation Division, 2001).

1.1 Basin Geology

The San Juan Basin is a typical asymmetrical, Rocky Mountain basin, with a gently dipping southern flank and a steeply dipping northern flank (Figure A1-2) (Stone et al., 1983). The Fruitland Formation is the primary coal-bearing unit of the San Juan Basin and the target of most coalbed methane production. Geologic cross sections showing generalized relationships between the Fruitland Formation and adjacent are shown in A1-4 through A1-6. The Fruitland coals are thick, with individual beds up to 80 feet thick. The Fruitland Formation is composed of interbedded sandstone, siltstone, shale, and coal. The stratigraphy of the Fruitland Formation is predictable throughout the basin, as follows:

- The thickest coalbeds are always found in the lower third of the formation;
- Pictured Cliffs Sandstone occurs immediately below the formation;
- Sandstone content is greater in the lower half; and
- Siltstone and shale predominate in the upper half (Choate et al., 1993).

The San Juan Basin may be subdivided into three unique regions, based on similar geologic, hydrologic, and production characteristics (Figure A1-7). These regions are denoted as Area 1, Area 2, and Area 3, and are described in more detail below (Kaiser and Ayers, 1994).

Area 1 consists of the northwestern quarter of the basin. Area 1 is characterized by the thickest (>20 feet) and highest-rank coal deposits in the San Juan Basin (Ayers et al., 1994). Most wells produce more than 1,000 cubic feet per day and several wells produce more than 15,000 cubic feet per day. Almost 90 percent of total methane production from the Fruitland Formation comes from three fields in a region of Area 1 known as the “Fairway” (Young et al., 1991; Ayers et al., 1994). Area 1 is an area of active recharge and in most places is hydrostatically over-pressured (greater than 0.50 pounds per square inch per foot). Wells in Area 1 usually produce moderate to large volumes of water, some of which meet the quality criteria of less than 10,000 milligrams per liter (mg/L) total dissolved solids (TDS) for an underground source of drinking water (USDW) (Kaiser et al., 1994).

Area 2 (the west-central region of the San Juan Basin) is hydrostatically under-pressured (0.30 to 0.50 pounds per square inch per foot) and is an area of regional groundwater discharge. Coalbeds are usually 7 to 15 feet thick, and occur primarily in northwest-trending belts that extend to the southwestern margin of the basin. Methane production from wells can be more than 100 thousand cubic feet per day, and a few wells produce 200 to 500 thousand cubic feet per day. Methane gas is produced water-free in this area as a consequence of the hydrostratigraphy and trapping mechanisms (Kaiser and Ayers, 1994). Additionally, Kaiser and Ayers (1994) suggest that water may be less mobile in the hydrophilic and low permeability coals. The Fruitland Formation in this area where it is under-pressured generally shows the presence of saline-type waters (Kaiser et al., 1994) that most likely have TDS concentrations greater than 10,000 mg/L, which does not meet the criteria for a USDW.

Area 3, the eastern region of the San Juan Basin, is hydrostatically under-pressured, and features low permeability and low hydraulic gradient, which suggests slow water movement within most of the aquifer. Only a few coalbed gas wells are located in this part of the basin, and they produce up to 8,000 cubic feet of methane per day, with little or no water content (Kaiser and Ayers, 1994). Produced waters from the Fruitland Formation in most of Area 3 have a high-salinity, resembling seawater (Kaiser and Ayers, 1994) in which TDS are too high to meet the water quality criteria of a USDW. However, along the southern margin of Area 3, TDS concentrations are less than 10,000 mg/L (Kaiser et al., 1994).

1.2 Basin Hydrology and USDW Identification

Tertiary sandstones and Quaternary alluvial deposits are present at the surface over much of the basin interior. These serve as the primary drinking water aquifers in the basin (Figure A1-2), and produced 55 million gallons per day in 1985 (Wilson, 1986). Cretaceous sandstones are an important source of water on the basin's periphery (Choate et al., 1993). The Paleocene Ojo Alamo Sandstone yields as much as 30 gallons per minute of potable water (Hale et al., 1965) and is mentioned as one of the primary drinking water aquifers of the region (Brown and Stone, 1979). Cleats and larger fractures in the Fruitland coals and the presence of interbedded permeable sandstones make the Fruitland Formation an aquifer and source of drinking water along the northern margin of the basin where TDS in the groundwater are less than 10,000. In most of Area 1, both the Fruitland Formation and the underlying upper Pictured Cliffs Sandstone act as a single hydrologic unit (Kaiser et al., 1994). The Fruitland and upper Pictured Cliffs Sandstone aquifer is underlain and confined by the low-permeability main Pictured Cliffs Formation and is overlain and partly confined by the Kirtland shale, which is up to 1,000 feet thick in the central basin. Overlying the Kirtland Formation is the Ojo Alamo Sandstone, (Figures A1-4, A1-5 and A1-6) which has been suggested as a possible source of groundwater for the municipality of Bloomfield (Stone et al., 1983). At Bloomfield, the coal and gas bearing Fruitland is separated from the Ojo Alamo aquifer by the Kirtland shale.

In the northern part of the basin, the Fruitland Formation and the underlying upper Pictured Cliffs Sandstone can be considered a single hydrogeologic unit on a regional scale because they exhibit the same hydraulic head and water quality characteristics and are the source of both the water and gas in the Pictured Cliffs sand tongues (Ayers and Zellers, 1994; Ayers et al., 1994). At the local scale, however, the two formations appear to exhibit poor hydraulic continuity, as evidenced by areas of over-pressuring (greater than 0.5 pounds per square inch per foot), abrupt changes in potentiometric surface (Figure A1-8), and upward flow (Kaiser et al., 1994). Discrete flow within individual units here is likely due to pinch out of thick, laterally extensive coal seams and truncation and offset of the beds by faults.

In general, groundwater is recharged along the Fruitland outcrops at the elevated, west, northern, and northwestern margins of the basin, and lateral flow converges primarily from the northeast and southeast toward upward discharge to the San Juan River valley (Kaiser et al., 1994). In the north, the Fruitland and upper Pictured Cliffs Sandstone aquifer system is confined by the overlying Kirtland shale, but it is poorly confined by the Kirtland in the central and southern portions of the basin. Water from the Fruitland discharges in the western part of the basin and migrates upward across the Kirtland shale into the Animas and San Juan Rivers (Stone et al., 1983). Generalized groundwater movement in the Fruitland system is shown in cross-section and plan view in Figures A1-9 and A1-10 (Kaiser and Swartz, 1988). The results of groundwater flow modeling for the entire basin (Kaiser et al., 1994) are shown in Figure A1-11.

In most of Area 1, the Fruitland system produces water containing less than 10,000 mg/L TDS, the water quality criteria for a USDW. Groundwater is usually freshest at the outcrop in recharge areas. The water dissolves salts and mixes with formation water as it flows, and the groundwater becomes increasingly saline as distance from the recharge source increases. The presence of low-salinity water at given locations in the San Juan Basin usually marks close proximity to the recharge source or the most permeable flow paths and implies a dynamic, active aquifer system (Kaiser et al., 1994). Figure A1-12 shows the chloride concentration of groundwater in the Fruitland Formation, and indicates that water nearest the northern recharge areas has a low dissolved solids and chloride content. Kaiser et al. (1994) reported that wells in the northern part of Area 1 produced water containing from 180 to 3,015 mg/L TDS. This was found to be the case over large portions of Area 1, especially within freshwater plumes resulting from areas of high permeability or fracture trends (Kaiser and Swartz, 1990; Oldaker, 1991).

Kaiser et al. (1994) conducted a water-quality sampling program in the San Juan Basin. Analyses taken from Fruitland coal wells in Area 1 show that the majority of wells (16 of 27 wells) produce water containing less than 10,000 mg/L TDS, (Figures A1-13a and A1-13b), although some nearby wells thought to be in less permeable zones produce water with higher TDS concentrations up to 23,000 mg/L (Kaiser et al., 1994). The boundary between waters with more and less than 10,000 TDS has not been published. Another group of wells throughout the same area was also sampled, but these wells were completed (constructed) in the adjacent and underlying Pictured Cliffs Sandstone bodies, which are in hydrologic communication with the Fruitland system (Kaiser et al., 1994).

Although from the above information it would seem that the Fruitland would be classified a USDW, the following additional information about disposal of brackish water produced along with the methane would seem to indicate that most of the water in the Fruitland would not meet the TDS criteria for USDW. Coalbed methane wells in the San Juan Basin produced from 0 to over 10,500 gallons of water per day, which contain from less than 300 mg/L TDS to over 25,000 mg/L (Kaiser et al., 1994; Kaiser and Ayers, 1994). Brackish water of various TDS concentrations and brine are produced in the over-pressured Area 1 of the basin while virtually no water is produced from coalbed methane wells in Areas 2 and 3 of the basin. Cox (1993) reported "Water disposal in the San Juan basin is a significant, long-term issue." In 1992, coalbed methane wells produced over 5 million gallons of water per day, and production was expected to increase to over 7.5 million gallons per day by 1995 (Cox, 1993). Produced water is disposed of by means of evaporation ponds, or, more commonly, by Class II injection into deeper zones such as the Entrada and Bluff sandstones, Morrison Formation, and Mesa Verde sandstone (Kaiser and Ayers, 1994). The authors estimated that injection wells cost up to \$2 million each and Cox (1993) reported that 51 of them had been constructed in the basin by 1993.

Area 2 is primarily an area of groundwater discharge. The Fruitland coals and Pictured Cliffs Sandstone in Area 2 are in hydraulic communication and behave as a single aquifer. The aquifer is under-pressured (less than 0.50 pounds per square inch per foot), transmits groundwater from the northeast and southeast, and eventually discharges to the

Animas and San Juan rivers. The TDS of most samples from Area 2 ranges from 10,000 to 16,000 mg/L (Kaiser et al., 1994).

The Fruitland system in most of Area 3 contains slow-moving water with salinity approximately equal to that of seawater, greater than 25,000 mg/L TDS, (Kaiser and Ayers, 1994). In Area 3, the Fruitland and Pictured Cliffs are separate, confined aquifers. In the southeastern one-third of Area 3, the Kirtland shale is absent because of Tertiary-age erosion, and the Fruitland and Ojo Alamo Sandstone could be in hydraulic communication with one another (Figure A1-6). In this area Tertiary rocks, including the Ojo Alamo, are mapped by the United States Geological Survey (Figure A1-14) as an aquifer having water with TDSs ranging from 500 to 1,000 mg/L (Lyford, 1979).

At the basin's southern margin in Area 3, downward flow occurs from the Ojo Alamo through the Kirtland shale to the poorly confined Fruitland aquifer through which it then moves southward to outcrops at a lower elevation and northward to the San Juan River Valley (Kaiser et al., 1994) (Figure A1-11). Twenty-four of 26 water samples from the Fruitland/Pictured Cliffs aquifer system in the south margin of the basin reported by Kaiser and Swartz (1994) had less than 9,000 mg/L TDS (Figure A1-13e & A1-13f). Groundwater in the Fruitland Formation at the southern margin of the basin has less than 10,000 mg/L TDS because most recharge there comes from above the Kirtland formation, rather than from southward throughput from the Fruitland Formation.

1.3 Coalbed Methane Production Activity

Coalbed methane production occurs primarily in coals of the Fruitland Formation. However, some methane is absorbed in the underlying and adjacent Pictured Cliffs Sandstone, therefore many wells are completed in both zones. About 2,550 wells were operating in the San Juan Basin in 2001 (CO Oil and Gas Conservation Commission and NM Oil Conservation Division, 2001). All wells are vertical wells that range from about 500 to 4,000 feet in depth, and were drilled using water or water-based muds. Almost every well has been fracture-stimulated, using either conventional hydraulic fracturing in perforated casing or cavitation cycling in open holes (Palmer et al., 1993b). Total gas production was 925 Bcf in 2000 (GTI, 2002).

Cavitation cycling is a fracturing method unique to a small area of the north-central San Juan Basin called the "Sweet Spot," or Fairway, of Area 1 (Figure A1-15). Almost half of all San Juan wells are located within the Fairway area and utilize open-hole completions (no casing across the production interval) and cavitation cycling. Cavitation cycling is used in this area because coals are: 1) very thick (individual coals over 40 feet thick); 2) hydrostatically over-pressured (0.5 to 0.7 pounds per square inch per foot); and 3) relatively more permeable than the rest of the basin (and coals in other basins) (Palmer et al., 1993b). This method uses several mechanisms to link the wellbore to the coal fracture system. Cavitation cycling:

- Creates a physical cavity in the coals of the open-hole section (up to 10 feet in diameter);
- Propagates a self-propping, vertical, tensile fracture that extends up to 200 feet away from the wellbore (parallel to the direction of least stress); and
- Creates a zone of shear stress-failure that enhances permeability in a direction perpendicular to the direction of least stress (Palmer et al., 1993a; Khodaverian and McLennan, 1993) (Figure A1-16).

Cavitation is accomplished by applying pressure to the well using compressed air or foam, and then abruptly releasing the pressure. The over-pressured coal zones provide a pressure surge into the wellbore (a “controlled blowout”), and the resulting stress causes dislodgement of coal chips and carries the chips up the well. These cycles of pressure and blowdown are repeated many times over a period of hours or days, and the repeated, alternating stress-shear failure in the coal formation creates effects that extend laterally from the wellbore (Kahil and Masszi, 1984). The resulting vertical fracture is tensile in origin, that is, it results from a “pulling” force rather than the compressive forces that create conventional hydraulic fractures. Because the fracture is tensile in origin, the height of the fracture does not usually extend out of the target coal seam (Logan et al., 1989).

Wells outside the Fairway area utilize cased-hole, perforated completions that employ conventional hydraulic fracturing (Holditch, 1990). Palmer et al. (1993a) reported that hydraulic fracturing in the San Juan Basin uses between 55,000 to 300,000 gallons of stimulation and fracturing fluids and between 100,000 to 220,000 pounds of sand proppant. In the San Juan Basin, geologic conditions in conjunction with fracturing techniques usually produce vertical fractures much longer than they are high, for example, up to 400 feet radially and less than 150 feet high (e.g., Colorado 32-7 No. 9 well, La Plata County, CO; Mavor et al., 1991). The primary reasons for the controlled height of San Juan coalbed fractures are the thickness and close spacing of coal seams (obviating the need for excessive height), and the presence and petro-physical properties of the overlying Kirtland shale (which prevents inadvertent fracture excursion out of the Fruitland) (Jeu et al., 1988; Logan et al., 1989; Palmer and Kutas, 1991). Holditch (1993) reports that where the coal seam is not overlain by shale, hydraulic fractures in the San Juan Basin can grow into overlying beds.

Fassett (1991) found that coalbed methane could migrate into overlying USDWs near the northern outcrop, in areas where confining shale layers are absent. Because of these factors, hydraulic fracturing in the San Juan Basin may indirectly impact overlying USDWs near the Fruitland outcrop at the basin margins, where USDWs are in closer proximity and the Kirtland shale may be eroded. Near the northern and northwestern recharge zones, groundwater usually contains less than 3,000 mg/L TDS (Kaiser et al., 1994; Cox et al., 1995).

Fracturing and stimulation fluids utilized in the northern San Juan Basin include (Figure A1-17 and Table A1-1):

- Hydrochloric acid (12% to 28% HCl);
- Plain water;
- Slick water (water mixed with solvent);
- Linear gels (water and a thickener such as guar-gum or a polymer);
- Cross-linked gels with breakers (gels with additives to prevent fluid leak-off from the fracture, and “breaker” chemicals to reduce viscosity so that the gel can be produced back from the well after treatment); and
- Nitrogen and CO₂ foam (75 percent gas, 25 percent water or slick water, plus a foaming agent) since about 1992 (Harper et al., 1985; Jeu et al., 1988; Holditch et al., 1989; Palmer et al., 1993a; Choate et al., 1993)

Oilfield service companies supply the stimulation fluid used to fracture the well as part of the service. The chemical composition of many fracturing fluids may be proprietary, and EPA was unable to find complete chemical analyses of any fracturing fluids in the literature. Table A1-1 presents some data from the literature concerning the general chemical makeup of common San Juan fracturing fluids (Economides and Nolte, 1989; Penny et al., 1991). In addition, most gel fluids utilize a breaker compound (usually borate or persulfate compounds or an enzyme, at 2 pounds/1,000 gallons) to allow post-treatment thinning and easier recovery of gels from the fracture (e.g., Jeu et al., 1988; Palmer et al., 1993a; Pashin and Hinkle, 1997).

Many of the compounds listed in Table A1-1 are quite hazardous in their undiluted form. However, these compounds are substantially diluted prior to injection. Coalbed methane development by fracturing, and stimulation in the San Juan Basin are regulated by the Colorado Oil and Gas Conservation Commission and the New Mexico Oil and Gas Board. Based on an analysis of current regulations, neither agency regulates the type or amount of fluids used for fracturing (Colorado State Oil and Gas Board Rules and Regulations 400-3, 2001; New Mexico Energy, Minerals and Natural Resources Department, Oil Conservation Division Regulations Title 19, Chapter 15, 2001).

About half of the coalbed methane wells in Area 1 are located in the Fairway zone and feature “cavitation-cycling” completions (Palmer et al., 1993a) (Figure A1-15). Therefore, about half of the wells in Area 1 have probably been stimulated using conventional fracture treatments. Based on the well density of Area 1 in 1990 (Figure A1-18) compared to the 2001 well population (2,550 wells), it is estimated that between 700 and 1,000 coalbed methane wells have been fracture-stimulated in the USDW of Area 1.

It has been shown that methane can migrate from gas wells into aquifers along the northern margin of the basin, but this condition was remediated with improved gas well construction (Cox et al., 1995). In addition, wells completed in other aquifers in the outcrop area have been shown to produce water chemically and isotopically similar to Fruitland wells, implying communication between the formations (Cox et al., 1995).

1.4 Summary

Coalbed methane development and hydraulic fracturing in some of the northern portions of the San Juan Basin take place within a USDW. The waters of the Fruitland-upper Picture Cliffs aquifer and producing zone in Area 1 usually contain less than 10,000 mg/L TDS. Most waters in the northern half of Area 1 contain less than 3,000 mg/L, and wells near the outcrop produce water that contains less than 500 mg/L.


Each fracture stimulation treatment may inject, on average, approximately 55,000 to 300,000 gallons of stimulation and fracturing fluid per treatment. There are no state controls on the type, composition, or volume of fracturing fluid employed in each well or treatment. In contrast to conventional gas formations, the anisotropic nature of fracture permeability, the volume of treatment fluids employed, and the height and proppant distribution in coalbed fractures may prevent the effective recovery of fracturing fluids during subsequent production.


The potential for fracturing to cause or allow degradation of water in aquifers adjacent to the producing zones seems relatively remote in the currently active gas producing fields, but the potential for such degradation varies in different parts of the basin. It has been shown that methane can migrate from gas wells into aquifers along the northern margin of the basin, but this condition was corrected with improved gas well construction. There is little potential for fracturing to create communication between the Fruitland-upper Picture Cliffs aquifer and the Ojo Alamo aquifer over much of the basin because the aquifers are separated by the poorly permeable Kirkland shale. However, the Kirkland varies greatly in thickness and forms a leaky hydrogeologic barrier when it is thinner. In the eastern part of the basin, the Kirkland Formation has been eroded and the Ojo Alamo lies disconformably and directly upon the Fruitland Formation, potentially allowing fracturing to cause hydraulic communication between the saline waters of the Fruitland and the fresh waters (500 to 1,000 mg/L) of the Ojo Alamo.


Table A1-1. Chemical Components of Typical Fracture/Stimulation Fluids Used for San Juan Coalbed Methane Wells


<u>Type of Stimulation Fluid</u>	<u>Composition</u>	<u>pH</u>
Hydrochloric acid	12% to 28% HCl water solution	<1-3
“Slick” water	miscible or immiscible solvent as viscosity reducer (% unknown)	NA
Diesel oil	NA	NA
Nitrogen and CO ₂ foam	75 % gas, 25 % water or slick water, plus a foaming agent)	NA
<u>Gels¹</u>		
R-F	3% resorcinol, 3% formaldehyde, 0.5% KCl, 0.4% NaHCO ₃	6.5
Pfizer Flocon 4800	0.4% xanthan, 154 ppm Cr ³⁺ (as CrCl ₃), 0.5% KCl	4.0
Marathon MARCIT	1.4% polyacrylamide (HPAM), 636 ppm Cr ³⁺ (as acetate), 1% NaCl	6.0
DuPont LuDox SM	10% colloidal silica, 0.7% NaCl	8.2
CPAM crosslinked with Pfizer Floperm 500	0.4% cationic polyacrylamide (CPAM), 1520 ppm glyoxal 2% KCl	7.3
Drilling Specialties HE-100 Crosslinked	0.3% HPAM-AMPS, 100 ppm Cr ³⁺ (as acetate), 2% KCl	5.0
Dowell YF-230	Hydroxypropylguar (HPG) x-linked with borate, persulfate with amine	NA

¹ Gels are typically mixed at a ratio of 40 lbs. per 1000 gal. water; compositions shown are “as mixed”.












Cross Section S-10 from Figure A1-3, a Stratigraphic Strike Section (Ayers and Ambrose, 1990)


Figure A1-4


7/14/01 wk 1027-SJA.00f




















Figure A1-11


7/14/01 WK 1027-SL-11.dxf


Equipotentials and Flow Paths from Ground Water Flow Modeling of the San Juan Basin
(Kaiser et al., 1994)














Cross-linked Gelled Sand Frac	
Water volume	2500 gal/ft of pay
Sand volume	5000 lbs/ft of pay
Type fluid	30# borate cross-linked gel
Type sand	40/70 mesh (1st 10% of job for fluid loss) 12/20 mesh (thereafter)
Avg. injection rate	55 BPM
Max. sand concentration	12 ppg
Pad volume	35% of total fluid pumped
Cost	\$50M-\$60M
Slick Water Sand Frac	
Water volume	4500 gal/ft of pay
Sand volume	3500 lbs/ft of pay
Type fluid	fresh water w/friction reducer
Type sand	20/40 mesh
Avg. injection rate	100 bpm
Max. sand concentration	6 ppg
Pad volume	66% of total fluid pumped
Cost	\$25M-\$35M
Foam Frac (gelled water)	
Water volume	2000 gal/ft of pay
Sand volume	5000 lbs/ft of pay
Type fluid	30# borate cross-linked gel
Type sand	100 mesh (1st 14% of job for fluid loss) 12/20 mesh (thereafter)
Avg. injection rate	40 BPM
Max. sand concentration	6 ppg
Pad volume	27% of total fluid pumped
Cost	\$100M-\$110M
Foam Frac (slick water)	
Water volume	2650 gal/ft of pay
Sand volume	3200 lbs/ft of pay
Type fluid	fresh water w/friction reducer
Type sand	40/70 mesh (1st 10% of job for fluid loss) 20/40 mesh (thereafter)
Avg. injection rate	90 BPM
Max. sand concentration	6 ppg
Pad volume	64% of total fluid pumped
Cost	\$75M-\$85M
Table of Fracture Stimulation Treatments in the Fruitland Formation of the San Juan Basin (Palmer et al., 1993)	
<div>7/14/01 wk 1027-SJ-17.cdr</div> <div>Figure A1-17</div>	







REFERENCES

AAPG = American Association of Petroleum Geologists
SPE = Society of Petroleum Engineers

Ayers, W.B., Ambrose, W.A., and Yeh, J.S. 1994. Coalbed methane in the Fruitland Formation – depositional and structural controls on occurrence and resources. New Mexico Bureau of Mines and Minerals Bulletin 146: Coalbed methane in the upper Cretaceous Fruitland Formation, San Juan Basin, New Mexico and Colorado, pp. 13-40.

Ayers, W.B. and Zellers. 1994. Coalbed methane in the Fruitland Formation, Navajo Lake area – geologic controls on occurrence and producibility. New Mexico Bureau of Mines and Minerals Bulletin 146: Coalbed methane in the upper Cretaceous Fruitland Formation, San Juan Basin, New Mexico and Colorado, pp. 63-86.

Brown, D.R. and Stone, W.J. 1979. Hydrogeology of the Aztec quadrangle, San Juan county, New Mexico. New Mexico Bureau of Mines and Mineral Resources (Sheet 1).

Choate, R., Lent, T., and Rightmire, C.T. 1993. Upper Cretaceous geology, coal, and the potential for methane recovery from coalbeds in the San Juan Basin – Colorado and New Mexico. AAPG Studies in Geology, 38:185-222.

Colorado State Oil and Gas Board Rules and Regulations 400-3, 2001.

Colorado Oil and Gas Conservation Commission and New Mexico Oil Conservation Division. 2001. Personal communication with staff.

Cox, D.O. 1993. Coal-seam water production and disposal, San Juan Basin. Quarterly Review of Methane from Coal Seams Technology, 11(2): 26-30 (December).

Cox, D.O., Young, G.B.C., and Bell, M.J. 1995. Well testing in coalbed methane (cbm) wells: an environmental remediation case history. Society of Petroleum Engineers Paper No. 30578, Proceedings 1995 SPE Technical Conference (Dallas), pp. 467-500.

Economides, M.J. and Nolte, K.G. 1989. Reservoir Stimulation, Second Edition, Prentice-Hall, New Jersey.

Fassett, J.E. 1991. The mystery of the escaping gas: forensic geology in the northern San Juan Basin, La Plata County, Colorado. USGS – AAPG Association Roundtable, p. 1223.

- Gas Technology Institute (GTI) Web site, 2002. Drilling and Production Statistics for Major US Coalbed Methane and Gas Shale Reservoirs.
<http://www.gastechnology.org>
- Hale, W.E., Reiland, L.J., and Beverage, J.P. 1965. Characteristics of the water supply in New Mexico. New Mexico State Engineer, Technical Report 31.
- Harper, T.R, Hagans, J.T., and Martins, J.P. 1985. Fracturing without proppant. SPE 13858, Proceedings SPE Low Permeability Reservoirs Symposium (Denver), p. 83.
- Holditch, S.A., Ely, J.W., Semmelbeck, M.E., Carter, R.H., Hinkle, J., and Jeffrey, R.G. 1989. Enhanced recovery of coalbed methane through hydraulic fracturing. SPE Paper 18250, Proceedings 1988 SPE Annual Technical Conference and Exhibition (Production Operations and Engineering), p. 689.
- Holditch, S.A. 1990. Completion methods in coal seam reservoirs. SPE 20670, Proceedings 65th SPE Annual Technical Conference (New Orleans), p. 533.
- Holditch, S.A. 1993. Completion methods in coal-seam reservoirs. Journal of Petroleum Technology, 45(3): 270-276 (March).
- Jeu, S.J., Logan, T.L., and McBane, R.A. 1988. Exploitation of deeply buried coalbed methane using different hydraulic fracturing techniques. SPE Paper 18253, Proceedings 63rd Annual Technical Conference (Houston).
- Kahil, A. and Masszi, D. 1984. Cavity stress-relief method to stimulate demethanation boreholes. SPE Paper No. 12843, Proceedings 1984 SPE Unconventional Gas Recovery Symposium (Pittsburg).
- Kaiser, W.R. and Swartz, T.E. 1988. Hydrology of the Fruitland Formation and coalbed methane producibility, *In* Geologic evaluation of critical production parameters for coalbed methane resources, Part 1: San Juan Basin. Annual Report to the Gas Research Institute, GRI-88/0332.1, pp. 61-81.
- Kaiser, W.R. and Swartz, T.E. 1990. Hydrodynamics of the Fruitland Formation. *In* Geologic Evaluation of critical production parameters for coalbed methane resources, Part 1: San Juan Basin. Annual Report for 1990, Gas Research Institute, GRI-90/0014.1, pp. 99-126.
- Kaiser, W.R. and Ayers, W.B. Jr. 1994. Coalbed methane production, Fruitland Formation, San Juan Basin: geologic and hydrologic controls. New Mexico Bureau of Mines and Minerals Bulletin 146: Coalbed methane in the upper Cretaceous Fruitland Formation, San Juan Basin, New Mexico and Colorado, pp. 187-207.

- Kaiser, W.R., Swartz, T.E., and Hawkins, G.J. 1994. Hydrologic framework of the Fruitland Formation, San Juan Basin. New Mexico Bureau of Mines and Minerals Bulletin 146: Coalbed methane in the upper Cretaceous Fruitland Formation, San Juan Basin, New Mexico and Colorado, pp. 133-164.
- Khodaverian, M. and McLennan. 1993. Cavity completions: a study of mechanisms and applicability. Proceedings of the 1993 International Coalbed Methane Symposium (Univ. of Alabama/Tuscaloosa), pp. 89-97.
- Logan, T.L, Clark, W.F., and McBane, R.A. 1989. Comparing open-hole cavity and cased hole hydraulic fracture completion techniques, San Juan Basin, New Mexico. SPE Paper 19010, Proceedings SPE Low Permeability Reservoirs Symposium (Denver).
- Lyford, F.P., 1979. Ground Water in the San Juan Basin, New Mexico and Colorado, USGS Water-Resources Investigations 79-73, 22p.
- Mavor, M.J., Dhir, R., McLennan, J.D., and Close, J.C. 1991. Evaluation of the hydraulic fracture stimulation of the Colorado 32-7 No. 9 well, San Juan Basin. Rocky Mountain Association of Geologists Guidebook, "Coalbed methane of Western North America", Fall Conference and Field Trip, pp. 241-249.
- New Mexico Bureau of Mines and Minerals. 1993. Atlas of Rocky Mountain Gas Reservoirs, p. 122.
- New Mexico Energy, Minerals and Natural Resources Department, Oil Conservation Division Regulations Title 19, Chapter 15,
<http://www.emnrd.state.nm.us/ocd/OCDRules/Oil&Gas/rulebook/rulebook.pdf>, 2001.
- Oldaker, P.R. 1991. Hydrogeology of the Fruitland Formation, San Juan Basin, Colorado and New Mexico. *In* Coalbed methane of Western North America. Rocky Mountain Association of Geologists, pp. 61-66.
- Palmer, I.D. and Kutas, G.M. 1991. Hydraulic fracture height growth in San Juan Basin coalbeds. SPE 21811, Proceedings SPE Low Permeability Reservoirs Symposium (Denver).
- Palmer, I.D., Lambert, S.W., and Spitler, J.L. 1993a Coalbed methane well completions and stimulations. Chapter 14 in AAPG Studies in Geology 38, pp. 303-341.
- Palmer, I.D., Mavor, M.J., Spitler, J.L., Seidle, J.P., and Volz, R.F. 1993b. Openhole cavity completions in coalbed methane wells in the San Juan Basin. *Journal of Petroleum Technology*, 45(11):1072-1080 (November).

- Pashin, J.C. and Hinkle, F. 1997. Coalbed Methane in Alabama. Geological Survey of Alabama Circular 192, 71pp.
- Penny, G.S, Conway, M.W., McBane, R. 1991. Coordinated laboratory studies in support of hydraulic fracturing of coalbed methane. Proceedings, 1991 SPE Annual Technical Conference and Exhibition (Sigma Reservoir Engineering), 66, pp. 231-246.
- Stevens, S.H., Kuuskraa, J.A., and Schraufnagel, R.A. 1996. Technology spurs growth of U.S. coalbed methane. Oil and Gas Journal, pp. 56-63 (January).
- Stone, W.J., Lyford, F.P., Frenzel, P.F., Mizell, N.H. and Padgett, E.T. 1983. Hydrogeology and water resources of San Juan Basin, New Mexico. New Mexico Bureau of Mines and Mineral Resources, Hydrologic Report 6, 70 p.
- Wilson, B. 1986. Water Use in New Mexico. New Mexico State Engineer Technical Report 46, 84 p.
- Young, G.B.C., McElhiney, J.E., Paul, G.W., and McBane, R.A. 1991. An analysis of Fruitland coalbed methane production, Cedar Hill field, northern San Juan Basin; SPE Paper No. 22913, Proceedings SPE Annual Technical Conference and Exhibition (Dallas).